# WALL RACK





## **G1 SERIES**





Master Key w/logo

Roller



**Mounting Pole** 





Hinge w/logo

Two Plies Steel





\* Order No. for Black Color : G1-XXXXXB

### **FEATURES**

- Designed and Manufactured To comply Standards of ANSI/EIA-310D-1992 (Rev.EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part:2, DIN 41494, 19" Standard.
- ♦ 3-Part Designed Front Door, Central Part and Back Base.
- Manufactured Made from 1.2mm Electro-Galvanized Steel Sheet and 2.0mm for mounting pole, 100% rust proof.
- Mounting Pole Designed to be L-shape angle with 10x10mm square punching hole to increase strength and flexible to adjust freely with screened Rack unit (U) on the mounting pole.
- Front Door
  - For G1-XXXXX model was the steel frame with acrylic 5.0mm thickness and 38 cm width, with film protection (About the height will follow as the size of Rack unit). Door edge with 3-fin type of dust proof rubber seal (Gray color). Support security lock with 19" Germany master key, and trademark embossing on the top.
  - For G1-XXXXXP model was the steel with perforated capsule ventilation surrounding for 50% of door's area.
- Central Part There is sliding rail to adjust the mounting pole. The bottom equipped with special rollers for opening and locking to back base part. The top has pre-punch fan pattern for mounting the fan sets (1-3 fan sets for installation). The both side have ventilation grill and support security locking system with 19" Germany master key same as the front door.
- Back Base There is the clip with 10x10mm for cable access at the top and bottom and can be mounting to the wall with screws by 2.4mm thickness two plies steel on the rear part.
- Hinge Made from 3 pieces of special high strength PVC (ABS) or other materials (as requested), without disturbance noise and rust-free. The front and rear door can reverse to change the opening direction from the left or right side by adjusting screw at the nut of hinge.
- Grounding System 2.5mm copper wire with yellow and green color stripe which connect between cabinet's structure and door.
- New Shine Light Gray Two-tone color painted by Electrostatic powder coating process for scratch resistance.
- Screw Set Provided screws, captive nuts, plastic washer with nickel plating and M6 standard.
- Manufacturer and Distributor Certified by ISO 9001:2015.

### **Options**

Color : \*Black or other (as requested)
Thickness : 1.6mm or other (as requested)

Pole : 4 Poles

### **Deliverly with**

- 3 Master key with key number and trademark embossing
- 4 Sets of wall mounting screw.
- Nut and screw sets according to no. of Rack unit (U).

#### ORDERING INFORMATION W=Width 600 mm. Standard

1U	Overall nm. Height (mm.)	Order No. of Different Depth (mm.)			Figure
= 44.45 mm.		D = 400	D = 500	D = 600	rigure
6U	320	G1-60406	G1-60506	G1-60606	
9U	455	G1-60409	G1-60509	G1-60609	Α
12U	590	G1-60412	G1-60512	G1-60612	
6U	320	G1-60406P	G1-60506P	G1-60606P	
9U	455	G1-60409P	G1-60509P	G1-60609P	В
12U	590	G1-60412P	G1-60512P	G1-60612P	

Sample: G1-60609B Wall Rack 9U, 60 x 60 cm., Black Color

## WALL RACK





### **G2 SERIES**





Master Key w/logo

Roller



**Mounting Pole** 





Hinge w/logo

Two Plies Steel



\* Order No. for Black Color : G2-XXXXXB

### **FEATURES**

- Designed and Manufactured To comply Standards of ANSI/EIA-310D-1992 (Rev.EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part:2, DIN 41494, 19" Standard.
- ♦ 3-Part Designed Front Door, Center Part and Back Base.
- Manufactured Made from 1.2mm Electro-Galvanized Steel Sheet and 2.0mm for mounting pole, 100% rust proof.
- Mounting Pole Designed to be L-shape angle with 10x10mm square punching hole to increase strength and flexible to adjust freely with screened Rack unit (U) on the mounting pole.
- Front Door It was the steel frame with acrylic 5.0mm thickness and 38cm width, with film protection (About the height will follow as the size of Rack unit) and perforated capsule surrounding for ventilation. Door edge with 3-fin type of dust proof rubber seal (Gray color). Support security lock with 19" Germany master key, and trademark embossing on the top.
- Center Part There is sliding rail to adjust the mounting pole. The bottom equipped with special rollers for opening and locking to back base part. The top has pre-punch fan pattern for mounting the fan sets (1-3 fan sets for installation). The both side have ventilation grill and support security locking system with 19" Germany master key same as the front door.
- Back Base There is the clip with 10 x 10mm for cable access at the top and bottom and can be mounting to the wall with screws by 2.4mm thickness two plies steel on the rear part.
- Hinge Made from 3 pieces of special high strength PVC (ABS) or other materials (as requested), without disturbance noise and rust-free. The front and rear door can reverse to change the opening direction from the left or right side by adjusting screw at the nut of hinge.
- Grounding System 2.5mm copper wire with yellow and green color stripe which connect between cabinet's structure and door.
- New Shine Light Gray Two-tone color painted by Electrostatic powder coating process for scratch resistance.
- Screw Set Provided screws, captive nuts, plastic washer with nickel plating and M6 standard
- Manufacturer and Distributor Certified by ISO 9001:2015.

### **Options**

Color : \*Black color or other (as requested)
Thickness : 1.6mm or other (as requested)

Pole : 4 Poles

### **Deliverly with**

- 3 Master key with key number and trademark embossing
- 4 Sets of wall mounting screw.
- Nut and screw sets according to no. of Rack unit (U).

### ORDERING INFORMATION W=Width 600 mm. Standard

1U	Overall Height (mm.)	Order No. of Different Depth (mm.)			
= 44.45 mm.		D = 400	D = 500	D = 600	
6U	320	G2-60406	G2-60506	G2-60606	
9U	455	G2-60409	G2-60509	G2-60609	
12U	590	G2-60412	G2-60512	G2-60612	

Sample: G2-60609B Wall Rack 9U, 60 x 60 cm., Black Color